

FERRI®

www.ferri-america.com



ME

Mowers

• Grass • Tractors from 20 to 30 HP

ME 125  20 to 25 HP  4'1"

ME 155  25 to 30 HP  5'1"




Mowers

• Grass • Twigs • Tractors from 20 to 30 HP



These mowers are designed for cutting grass, brambles in parks, sport grounds, lawns: they are preferable for their low power requirements and their reduced overall dimensions.

Equipment	MODEL	ME 125	ME 155
Center mount		●	●
Rear adjustable roller		●	●
Adjustable belt-tension		●	●
Rotor with internal		●	●
Double skin		●	●
Three point linkage Cat. I		●	●
Cast iron gear box		●	●
Belt		●	●
 Articulated "Y" blades max cut 1"		●	●

● Standard □ Optional



Strong points



Adjustable belt tension.



Rear adjustable roller



Rotor internal sealed bearings

Technical specifications

Mod.		ME 125	ME 155
Cutting width	ft	4'1"	5'1"
Weight	lbs	353	397
Rotor with articulated blades "Y"	No	56	72
Tractor required power- Engine H.P.	RPM	540	540
	min-max HP	20-25	25-30

Working positions

ME 125	24"	25"
ME 155	29"	31"



FERRI srl Via C. Govoni, 30 - 44034 Tamara (FE) Italy
 Tel. 011-39-0532.866866 - Fax 011-39-0532.866851 - www.ferrisrl.it - info@ferrisrl.it

Customer Service / FERRI:

John Fisher
 PO Box 127
 Lake Oswego, OR 97034 USA
 Phone 503.675.1070
 Fax 503.699.4170
 ferri.america@comcast.net
 www.ferri-america.com

All data subject to change.

Campbell 6348 ME210A REV.04 09/08